

DH-HAC-HDW1200TQ(-A)

2MP HDCVI Quick-to-install IR Eyeball Camera



- Max 30fps@1080P
- Quick-to-install eyeball saves installation time
- CVI/CVBS/AHD/TVI switchable
- 3.6mm fixed lens (2.8mm, 6mm optional)
- Built-in mic(-A)
- Max. IR length 40m, Smart IR
- IP67, DC12V



System Overview

Experience 1080P full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 1080P HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Easy Installation

HDCVI Quick-to-install eyeball adopts quick-to-install pedestal, which can achieve easier installation than conventional eyeball. Quick-to-install camera reduces time and labor costs.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 800m(1080p)/1200m(720P) transmission via coaxial cable, and up to 300m(1080P)/450m(720P) via UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments.

With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments.

Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification						WDR		DWDR	
Camera						White Balance		Auto; manual	
Image Sensor		1/2.7 inch CMOS				Gain Control		Auto; manual	
Max. Resolution		1920(H)×1080(V)				Noise Reduction		2D NR	
Pixel		2MP				Smart IR		Yes	
Scanning System		Progressive				Electronic Defog		Yes	
Electronic Shutter Speed		PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s				Mirror		Off/On	
S/N Ratio		>65dB				Privacy Masking		Off/On (8 area, rectangle)	
Min. Illumination		0.02Lux/F1.9, 30IRE, 0Lux IR on				Certifications			
Illumination Distance		40 m (131.2 ft)				CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)			
Illuminator On/Off Control		Auto; manual				Port			
Illuminator Number		1				Audio Output			
Pan/Tilt/Rotation Range		Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°				One channel built-in mic (-A)			
Lens						Video Output			
Lens Type		Fixed-focal				Video output choices of CVI/TVI/AHD/CVBS by one BNC port			
Mount Type		M12				Power			
Focal Length		2.8 mm; 3.6 mm; 6 mm				Power Supply			
Max. Aperture		F1.9				12V ±30% DC			
Field of View		2.8 mm: 119° x 101° x 54° (diagonal x horizontal x vertical) 3.6 mm: 100° x 84° x 45° (diagonal x horizontal x vertical) 6 mm: 60° x 56° x 30° (diagonal x horizontal x vertical)				Power Consumption			
Iris Type		Fixed iris				Max 2.9W (12V DC, IR on)			
Close Focus Distance		2.8 mm: 0.5 m (1.7 ft) 3.6 mm: 0.8 m (2.6 ft) 6 mm: 2 m (6.6 ft)				Environment			
DORI Distance	Lens	Detect	Observe	Recognize	Identify	Operating Temperature			
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)			
	3.6 mm	49.7 m (163.1 ft)	19.9 m (65.3 ft)	9.9 m (32.5 ft)	5 m (16.4 ft)	Storage Temperature			
	6 mm	82.8 m (271.7 ft)	33.1 m (108.6 ft)	16.6 m (54.5 ft)	8.3 m (27.2 ft)	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)			
Video						Protection Grade			
Frame Rate		CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H				IP67			
Resolution		1080P (1920×1080); 720P (1280×720); 960H (960×576/960×480)				Structure			
Day/Night		Auto switch by ICR				Casing			
BLC		BLC/HLC/DWDR				Metal inner core+plastic cover+plastic pedestal			
						Camera Dimensions			
						φ109.9 mm × 100.9 mm (φ4.33" × 3.97")			
						Net Weight			
						0.32 Kg (0.71 lb)			
						Gross Weight			
						0.49 Kg (1.08 lb)			

Ordering Information

Type	Part Number	Description
2MP Camera	DH-HAC-HDW1200TQP 2.8mm	2MP HDCVI IR Eyeball Camera
	DH-HAC-HDW1200TQN 2.8mm	
	DH-HAC-HDW1200TQP 3.6mm	
	DH-HAC-HDW1200TQN 3.6mm	
	DH-HAC-HDW1200TQP 6mm	
	DH-HAC-HDW1200TQN 6mm	
	DH-HAC-HDW1200TQP-A 2.8mm	
	DH-HAC-HDW1200TQN-A 2.8mm	
	DH-HAC-HDW1200TQP-A 3.6mm	
	DH-HAC-HDW1200TQN-A 3.6mm	
	DH-HAC-HDW1200TQP-A 6mm	
	DH-HAC-HDW1200TQN-A 6mm	
Accessories	PFA13G	Junction box
	PFA130-E	IP66 Junction box
	PFB205W	Wall Mount Bracket (For use alone or with PFA152-E)
	PFA152-E	Pole Mount Bracket (For use with PFB204W)
	PFM800-E	Passive HDCVI Balun
	PFM321D	12V 1A Power Adapter
	PFM820	UTC Controller
	PFM904	Integrated Mount Tester

Accessories

Optional:



PFA13G
Junction box



PFA130-E
IP66 Junction box



PFB205W
Wall Mount Bracket
(For use alone or with
PFA152-E)



PFA152-E
Pole Mount Bracket
(For use with PFB204W)



PFM800-E
Passive HDCVI Balun



PFM321D
12V 1A Power Adapter



PFM820
UTC Controller



PFM904
Integrated Mount Tester

Junction Mount	Wall Mount	Pole Mount (Vertical)

Dimensions (mm[inch])

